

Item description : I288

Vacuum bench B2410 spraying system S8 and tank CO assembled and installed

The machine is composed by:-Vacuum bench created to contain even more the nebulized adhesive, equipped with a silent and powerful engine. -Spray gun G6 designed for both precise and large areas bonding. In particular it is possible to spray the glue from a minimum of 3 mm up to a maximum of 50 mm. -Stainless steel tank 10 lt. capacity treated with non-stick Teflon.

The bench set on wheels for an easy displacement inside the factory, has a front intake in addition to the usual one on the working plane. The spray gun is held up by an equalizer for making it easy to handle. It can be set going manually by pressing a lever or through a pedal so to leave the operator's hands free.



The operator, after starting the machine, can place the materials on the working plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty or when the vacuum bench is not intaking properly. To speed up the working process it is possible to use some nets in order to reduce the idle time due to loading and unloading the pieces on the working area. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

Specific:

Capacity m3 / h : 2400	Volt : 230	Prevalence : 270	Hertz : 50/60
Watt : 245	Bar exercise : 6	Decibel (dB) : 72/67	Ampere : 2,6
Air It / min : 30	Effective width cm : 109	Usable depth cm : 57	Average consumption :
Gross Weight kg : 93.660	Tare Kg : .000	Length mt : 0.75	Height mt : 1.75
Net Weight kg : 93.660	Net Weight kg :	mt Width : 1.15	Volume m3 : 1.483

Intercom Srl ® - P.iva e C.F. 06183210480 Address: Via della Gora, 13 - 50025 Montespertoli - Firenze - Italia Phone: +39 0571 671096 - Fax: +39 0571 671151 - Email: info@intercomsas.it - Web: www.intercomsas.it